





The EcoLite™ incorporates essential features with Casio's Industry Leading LampFree® Technology to create a budget friendly projector. The XJ-V2 delivers reliable long term operation, exceptional image quality, 3000 lumens of brightness & connectivity and is ideal for use in classrooms, on the road or in the boardroom.

LampFree Benefits:

- Laser & LED Hybrid Light source
- 20,000 estimate operating life
- Mercury Free
- No Lamp Replacement
- No Down Time
- Quick ON full brightness in 6 seconds
- Instant Off

Key Features:

- Laser & LED Hybrid Light source
- Brightness: 3000 lumens
- Resolution: XGA (1024 x 768)
- Display Device: 0.55" DLP® chip × 1, DLP® system
- Lens: 1.1 x Manual Zoom/FocusThrow Ratio: 1.54-1.71:1
- Terminals:
 - RGB (15 pin HD)
 - HDMI
 - RS-232 (9 pin D-Sub)
 - Audio (3.5mm stereo Mini Variable Audio Out
- Dimensions: 10.6"w x 10.6"d x 3.5"h
 Ceiling Mount: Yes Four (4) M4 x 4

Reliable Operation and Low TCO:

Casio LampFree® Projectors are reliable and built to last, with an estimated light source life of up to 20,000 hours. The EcoLite is covered by a 3-year parts and labor warranty plus 5 years or 10,000 hours on the Hybrid Light Source. Our industry leading warranty makes our already low Total Cost of Ownership (TCO) even better and users can expect to easily save up to \$1000 on lamp cost during the warranty period.



Native Resolution	XGA (1024 x 768) 786,432 pixels
Native Aspect Ratio	4:3
Brightness	3000 lumens
Display Device	0.55" DLP® chip
Contrast Ratio	20000:1
(Full White/Black)	1.4V.M
Lens Type	1.1X Manual Zoom & Focus
Lens Offset	72%
Light Source	Casio Laser & LED Hybrid
Estimated Light Source Life	Up to 20,000 hours
Projection Screen Size (Min-Max)	30 - 300 inches
Projection Range	E0 CE 6
60-inch Screen	5.9-6.5 ft
100-inch screen Minimum	10.1-11.2 ft 2.7 ft @30inch 1
Throw Ratio	
	1.54-1.71:1
Keystone Correction	Vertical + or - 30° (Manual)
Color Reproduction Power Source	Full color (up to 1.07 billion colors)
	AC 100 ~240V, 50/60 Hz
Power Consumption	120W Fee ON Lovel 1/150W F OFF Bright M.
Operating	120W Eco ON Level 1/150W Eco OFF Bright Mode
Standby Standby	0.12w (120V)
TERMINAL CONNECTIVITY	
Video Signal Compatibility	400D/F7CD/700D/4000/4000-7
HDMI Video Signal Input	480P/576P/720P/1080i/1080p/
Component Video Signal Input	480i/480p/576i/576p/720p/1080i/1080p
Maximum Computer Input	UXGA (1600 x 1200)
	Warini D. Cala 15 aire at also are a VCl CoNDl Daireast
RGB/Component Video Input	"mini D-Sub 15 pin x 1 also use as YCbCr/YPbPr input
HDMI	commercially available adapter required"
Composite Video	"HDMI Type A x 1 HDCP and audio support"
	No 3.5 mm Mini - Stereo
Audio Microphone	3.5 mm ivini - Stereo No
USB	No No
Wireless Capability	INO
OUTPUTS Audio	3.5 mm Mini - Stereo Variable Audio
RGB Output	No
AUDIO AND CONTROL SYSTEMS	IVO
Control Terminal	
RS-232	RS-232 (D-sub 9 Pin) x 1
IAN	
	No
OTHER INFORMATION	No
OTHER INFORMATION Usage Environment	·
OTHER INFORMATION Usage Environment Operating Temperature	41~95°F
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity	41~95°F 20~80% (non condensation)
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode	41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level)
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode	41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7)	41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection	41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours 90 degrees Up/Down only
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning	41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours 90 degrees Up/Down only No
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range	41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours 90 degrees Up/Down only No TBA
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility	41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours 90 degrees Up/Down only No TBA Kensington™ Compatible / Power On Password
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable	41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours 90 degrees Up/Down only No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws (Type x Qty)	41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours 90 degrees Up/Down only No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm)
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws (Type x Qty)	41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours 90 degrees Up/Down only No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty	41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours 90 degrees Up/Down only No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete details
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories	41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours 90 degrees Up/Down only No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete details Remote Control, Power Cord, RGB Cable, Warranty
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Optional Accessories	41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours 90 degrees Up/Down only No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete details Remote Control, Power Cord, RGB Cable, Warranty None
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Optional Accessories Optional Accessories Cabinet Color	41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours 90 degrees Up/Down only No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete details Remote Control, Power Cord, RGB Cable, Warranty
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Optional Accessories Optional Accessories Cabinet Color Dimension (W x D x H)	41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours 90 degrees Up/Down only No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete details Remote Control, Power Cord, RGB Cable, Warranty None White
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operatino (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Optional Accessories Cabinet Color Dimension (W x D x H) Including Projections	41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours 90 degrees Up/Down only No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, ser Warranty Statement included with product for complete details Remote Control, Power Cord, RGB Cable, Warranty None White
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Optional Accessories Cabinet Color Dimension (W x D x H) Including Projections Excluding Projections	41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours 90 degrees Up/Down only No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete details Remote Control, Power Cord, RGB Cable, Warranty None White 10.6" x 10.6" x 3.5" 10.6" x 10.6" x 3.3"
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Optional Accessories Optional Accessories Cabinet Color Dimension (W x D x H) Including Projections Excluding Projections Weight	41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours 90 degrees Up/Down only No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete details Remote Control, Power Cord, RGB Cable, Warranty None White
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable	41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours 90 degrees Up/Down only No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete details Remote Control, Power Cord, RGB Cable, Warranty None White 10.6" x 10.6" x 3.5" 10.6" x 10.6" x 3.3" 6.2 lbs
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Optional Accessories Optional Accessories Cabinet Color Dimension (W x D x H) Including Projections Excluding Projections Weight Packing Information Carton Dimensions	41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours 90 degrees Up/Down only No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) insert depth (5-8 mm) 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete details Remote Control, Power Cord, RGB Cable, Warranty None White 10.6" x 10.6" x 3.5" 10.6" x 10.6" x 3.3" 6.2 lbs
OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable	41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours 90 degrees Up/Down only No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete details Remote Control, Power Cord, RGB Cable, Warranty None White 10.6" x 10.6" x 3.5" 10.6" x 10.6" x 3.3" 6.2 lbs

© 2015 Casio America, Inc. All rights reserved. Casio is a registered trademark of Casio Computer Co., Ltd. In the United States and/or other countries. Specifications were thought to be correct at time of publication. All specifications and features are subject to change without notice. DLP, the DLP logo and the DLP medalillon are trademarks of lexas instruments. XGA and WXGA are registered trademarks of International Business Machines Corporation in the United States. HDMI is a trademark or registered trademark of HDMI Licensing, LLC. Other product names or company names on this specification brochure are either trademarks or registered trademarks of their respective owners.